Stormwater Summary Table (Required to be on the Plan)

s within the HUC						
ecimal Degrees						
that apply)	MS4		Wetlands		River/Stream/Ditch	
Pre Development	Pre Development		Post Development		Post Development	
Area (Sq. Ft.)	Area (%)		Area (Sq. Ft.)		Area (%)	
ha limita of diatumban						
ne umus oj aisturvano	te 					
		1				
			Required Reduction			
1 New Development			Phosphorus load cannot exceed .41 pounds per			
			1			
\geq 1 acre with no net increase in impervious cover.			20% Below pre-developed phosphorus load			
< 1 acre with no net increase in impervious cover.			10% Below pre-developed phosphorus load			
4 Net increase in impervious cover			1			
			increased impervious, criteria 2 or 3 based on the disturbance outside of new impervious area.			
5 Linear Davidenment musicate on mice davidened			1			
5 Linear Development projects on prior developed lands			20% Below pre-developed phosphorus load.			
al Required for site ((lhe/yr)·					
ar Required for site ((10 <i>s</i> / y1).					
	that apply) Pre Development Area (Sq. Ft.) The limits of disturbance irements Development Criterent to net increase in importance in impo	that apply) MS4 Pre Development Area (Sq. Ft.) Pre Divelopment Area (%) Pre Development Area (%)	that apply) MS4 Pre Development Area (Sq. Ft.) Pre Development Area (%) Pre Development Area (%)	that apply) MS4 Wetlands Pre Development Area (Sq. Ft.) Phe limits of disturbance Phosphorus load ca acre per year. Phosphorus load ca acre per year. Pro net increase in impervious cover. Pro Development Oriteria Requirement Phosphorus load ca acre per year. Pro net increase in impervious cover. Pro Development Area (Sq. Ft.) Pro Development Area (Sq. Ft.)	that apply) MS4 Wetlands Pre Development Area (Sq. Ft.) Me limits of disturbance Melimits o	

(If credits were purchased, please provide all required documents)

Stormwater Management Facility (BMP) The BMP Clearinghouse must be used for the design and designation of all Storm Water Management Facilities. The BMP(s) need to be labeled and numbered on the site plan. Is Low Impact Development Implemented? Yes No Has the BMP Maintenance Agreement been filed? Yes No										
BMP No.	Contributing Drainage Area (sq. ft.)	Type of BMP and DEQ Spec.	Eff. (%)	Phosphorus Removal (lb/yr)	Nitrogen Removal (lb/yr)	Water Quality Volume (cubic ft)	Water Quantity Volume (cubic ft)	Forest/Open Space (sq. ft.)	Managed Turf sq. ft.)	Impervious Surface (sq. ft.)
Total Phosphorus Removal Reduction for site (lbs/yr): Amount Phosphorus Removed in Excess for site (lbs/yr):										

Water Quantity Requirer	nents			
Channel Protection-Required j	for all sites.			
Discharge point	1 st Option	2 nd Option		
Manmade stormwater conveyance system	Prove post-development peak flow rate of 2-yr storm without causing erosion.	Energy Balance Equation		
Restored stormwater conveyance system	Prove that the development is functioning in accordance with design objectives.	Energy Balance Equation		
Natural stormwater conveyance system	Energy Balance Equation.	Not Available		
Project Condition and Option (I Condition	Please provide documentation on Plan Set): _/ Option			

If the Energy Balance Equation is not used, analysis needs to be completed to a point where:

- 1. The site's contributing drainage area is less than or equal to 1% of the total watershed
- 2. The site's peak flow rate from the 1-year storm is less than or equal to 1% of the existing peak flow rate. This analysis needs to be provided within the supplied calculations.

Flood Protection						
Discharge point	1 st Option	2 nd Option				
Concentrated stormwater that	Confine the post-development peak	Not Available				
does not experience local	flow rate for the 10-yr storm within					
flooding (10-yr storm)	the system.					
Concentrated stormwater that	Confine the post-development peak	Release a post development flow rate				
experiences local flooding (10-	flow rate for the 10yr- storm within	for the 10-yr storm event that is less				
yr storm)	the system.	than the predevelopment peak flow				
		rate for the 10-yr storm.				
Project Condition and Option: Condition / Option (Please provide documentation within calculation or on the Plan Set)						
Pre-developed flow (cfs): Post-developed flow (cfs):						
Analysis needs to be completed to a point where: 1. The site's contributing drainage area is less than or equal to 1% of the total watershed 2. The site's peak flow rate from the 10-year storm is less than or equal to 1% of the existing peak flow rate from the 10-yr storm prior to implementing control measures. 3. The stormwater conveyance system enters a mapped floodplain.						